



# Exit and Emergency Combo LED Lightpipe

## FEATURES

- Easy to install, snap together design
- Remote capable- up to 2 CLED remote heads
- Universal style – includes 2 face plates, a back plate and mounting canopy
- Compact, low profile design
- Charge rate/power "ON" LED indicator light with test button
- Low voltage disconnect eliminates deep discharge
- Brown-out, short circuit and voltage surge protection
- Overcharge protection
- UL recognized maintenance-free NiCad battery
- Universal J-Box mounting system – Ceiling, wall or end mount
- UL listed 90 minute emergency run time, 24 hour recharge time
- Constant, uniform illumination by long-life, high intensity, red or green LEDs
- Unique, adjustable "Light Bar" emergency lighting with ultra-bright, energy efficient white LEDs
- Rugged, injection-molded UL94 V-0 flame retardant, high-temperature thermoplastic housing
- Fully-illuminated 6" characters with 3/4" stroke
- Optional Self Test/Self Diagnostics (SDT) available
- Chevron-style, universal arrow knockouts
- 120/277V dual primary, 60Hz input
- 4.5 Watt (36 LEDs x 0.125 Watt) per head
- Standard finishes: Black and white
- UL Listed for damp location
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

## WARRANTY

Any component that fails due to manufacturers defect is guaranteed for 3 years with a separate 5 year pro-rated warranty on the battery. The warranty does not cover physical damage, abuse or acts of God. Manufacturer reserves the right to charge for such repairs if deemed necessary.

## ORDERING INFORMATION

Series	Style	Finish	Options
SD-02-CLP2RW-RC	2 = UNIVERSAL	W = WHITE	SDT = SELF TEST / DIAGNOSTICS
SD-02-CLP2GW-RC		B = BLACK	



This fixture offers maintenance-free, long life dependable service, and easily mounts above doors and in restricted spaces to fit any application. Unique "Light Bar" design combines LED exit illumination with reliable, low-profile LED emergency lighting.

## DIMENSIONS

